Mars Global Surveyor Thermal Emission Spectrometer

Time Sequential Data Record Standard Product Archive Volume Software Interface Specification

(TES-TSDR Archive Volume SIS)

Version 2.3 October 1, 2000

J. D. Bowman

E. A. Guinness

S. Slavney

R. E. Arvidson

Washington University

St. Louis, Missouri 63130

Mars Global Surveyor Thermal Emission Spectrometer

Time Sequential Data Record Standard Product Archive Volume Software Interface Specification

(TES-TSDR Archive Volume SIS)

Version 2.3 October, 2000

Approved:		
11	Philip R. Christensen	Date
	TES Principal Investigator	
	Greg L. Mehall	Date
	TES Instrument Manager	
	Thomas Thorpe	Date
	Mars Global Surveyor Science Office Manager	Duic
	2.2223 2.3341 Surveyor Science Strice Manager	
	Yolanda Fletcher	Date
	PDS / Mars Global Surveyor Interface Manager	

TABLE OF CONTENTS

1. Pre	face	1	
1.1	Acronyms and Abbreviations		
1.2	2. Glossary	1	
2. Intr	roduction	2	
2.1	. Content Overview	2	
2.2	2. Scope	3	
2.3	3. Applicable Documents	3	
3. Arc	chive Volume Contents	3	
3.1	. ROOT Directory Contents	4	
3.2	CATALOG Directory Contents	4	
3.3	B. DATA Directory Contents	5	
3.4	DOCUMENT Directory Contents	8	
3.5	5. INDEX Directory Contents	8	
3.6	5. SOFTWARE Directory Contents	9	
4. Arc	chive Volume Format	9	
4.1	. Disk Format	9	
4.2	P. File Formats	9	
	4.2.1. Catalog File Format	9	
	4.2.2. Document File Format	10	
	4.2.3. PDS Label Format	10	
	4.2.4. Software File Format	11	
	4.2.5. Tabular File Format	11	
5. Arc	chive Volume Generation	12	
5.1	2 400 114115151, 1 4114115111151150115, 4114 11504511511		
5.2	2. Data Product Sizes	12	
5.3	5.3. Labeling and Identification		
6. Cognizant Persons and Support Staff			
APPENDIX A: Volume Directory Structure			

TABLES

- Table 1 TES-TSDR Standard Product Elements
- Table 2 TES-TSDR Standard Product Element Nominal Sizes
- Table 3 TES-TSDR Archive Volumes Support Staff

1. Preface

This document describes the format and content of the Thermal Emission Spectrometer Time Sequential Data Record (TSDR) Standard Product Archive Collection.

1.1. Acronyms and Abbreviations

ASCII American Standard Code for Information Interchange

CD-ROM Compact Disk - Read-Only Memory

CD-WO Write-Once Compact Disk

DVD Digital Versatile Disc

FFT Fast Fourier Transform

ISO International Standards Organization

JPL Jet Propulsion Laboratory

MB Megabytes

MGS Mars Global Surveyor

NSSDC National Space Science Data Center

PDB Project Database

PDS Planetary Data System

PSG Project Science Group

SDVT Science Data Validation Team

SFDU Standard Formatted Data Unit

SIS Software Interface Specification

TES Thermal Emission Spectrometer

TSDR Time Sequential Data Record

1.2. Glossary

Archive - An archive consists of one or more data sets along with all the documentation and ancillary information needed to understand and use the data. An archive is a logical construct independent of the medium on which it is stored.

Archive Volume, Archive Volume Set - A volume is a unit of media on which data products are stored; for example, one CD-ROM. An archive volume is a volume containing all or part of an archive; that is, data products plus documentation and ancillary files. When an archive spans

multiple volumes, they are called an archive volume set. Usually the documentation and some ancillary files are repeated on each volume of the set, so that a single volume can be used alone.

Catalog Information - High-level descriptive information about a data set (e.g. mission description, spacecraft description, instrument description), expressed in Object Description Language (ODL) which is suitable for loading into a PDS catalog.

Data Product - A labeled grouping of data resulting from a scientific observation, usually stored in one file. A product label identifies, describes, and defines the structure of the data. An example of a data product is a planetary image, a spectrum table, or a time series table.

Data Set - An accumulation of data products. A data set together with supporting documentation and ancillary files is an archive.Standard data product - A data product generated in a predefined way using well-understood procedures, processed in "pipeline" fashion. Data products that are generated in a nonstandard way are sometimes called special data products.

2. Introduction

2.1. Content Overview

The Thermal Emission Spectrometer (TES) is an instrument on the Mars Global Surveyor (MGS) orbiter. TES generates two types of standard products. This Software Interface Specification (SIS) describes the format, content, and generation of the TES Time Sequential Data Record (TSDR) Standard Product Archive Volumes for all MGS mission phases. Each TES-TSDR Standard Product consists of up to ten product elements stored in separate files. The product elements are listed in Table 1. Each element is organized in a time-ordered fashion.

Table 1 - TES-TSDR Standard Product Elements

Product Element	Contents
BOL	Raw and calibrated bolometer data
CMP	Raw complex data
GEO	Derived positional and geometric values
IFG	Raw interferogram data
LMB	Derived atmospheric limb observations
OBS	Observation parameters
POS	Raw positional and geometric data

RAD Raw and calibrated radiance data

SRF Derived surface observations

TLM Auxiliary observation parameters

2.2. Scope

The specifications in this document apply to all TES-TSDR Standard Product Archive Volumes that are produced during the Mars Global Surveyor mission.

2.3. Applicable Documents

ISO 9660-1988. April 1988 - CD-ROM format

Arvidson, R., E. Guinness, and S. Slavney, Mars Global Surveyor Project Archive Generation, Validation, and Transfer Plan, MGS Document #542-312, 1998.

Christensen, P. R., et al., Thermal Emission Spectrometer Experiment: Mars Observer Mission, J. Geophys. Res., 97, 7719-7734, 1992.

Mars Global Surveyor TES (Thermal Emission Spectrometer) Time Sequential Data Record (TSDR) Software Interface Specification (TES-TSDR SIS), August 24, 1998.

Planetary Science Data Dictionary Document, July 15, 1996, Planetary Data System, JPL D-7116, Rev. D.

Planetary Data System Data Preparation Workbook, February 1995, Version 3.1, JPL D-7669, Part 1.

Planetary Data System Standards Reference, July, 1995, Version 3.2. JPL D-7669, Part 2.

3. Archive Volume Contents

This section describes the contents of the TES Standard Product Archive Volumes, including the file names, file contents, file types, and organization responsible for providing the files. The complete directory structure is shown in Appendix A.

3.1. ROOT Directory Contents

The following files are contained in the ROOT Directory.

File Name	File Contents
AAREADME.HTM	Volume contents and format information in html format.
AAREADME.LBL	PDS label for aareadme html and ASCII documents.
AAREADME.TXT	Volume contents and format information in ASCII text.
ERRATA.TXT	Cumulative listing of comments and updates concerning all TES-TSDR Standard
	Products on all volumes published so far.
VOLDESC.CAT	Description of the contents of this volume in a PDS format readable by both
	humans and computers.

3.2. CATALOG Directory Contents

The files in the CATALOG directory provide a top-level understanding of the Mars Global Surveyor Mission, spacecraft, instruments, and data sets in the form of completed PDS catalog objects. The files in this directory are coordinated with the PDS data engineer.

File Name	File Contents
CATINFO.TXT	Description of the contents of this directory.
DATASET.CAT	PDS high-level data set catalog information for the TES-TSDR data set.
DEITGT.CAT	PDS high-level target information for the moon Deimos.
INST.CAT	PDS high-level instrument and personnel description.
INSTHOST.CAT	PDS high-level spacecraft description.
MARTGT.CAT	PDS high-level target information for the planet Mars.
MISSION.CAT	PDS high-level mission description.
PERSON.CAT	Cognizant persons and support staff for the TES instrument and archive.
PHOTGT.CAT	PDS high-level target information for the moon Phobos.
REF.CAT	Documents referenced by the catalog objects.

3.3. DATA Directory Contents

The following files are contained in the DATA Directory.

File Name	File Contents
DATAINFO.TXT	Description of contents of this directory.
ENB.TXT	TES team experimenter's notebook.
GEOMETRY.TXT	A list of the SPICE files used to calculate geometry records in this volume.
WAVNUMDS.LBL	PDS label for wavnumds.tab.
WAVNUMDS.TAB	Table of values for center wavenumber for each of the six detectors when TES is
	operated in double scan mode.
WAVNUMSS.LBL	PDS label for wavnumss.tab.
WAVNUMDS.TAB	Table of values for center wavenumber for each of the six detectors when TES is
	operated in single scan mode.

All TES-TSDR data products are split into ten elements based on the type of information they contain. Every element consists of a fixed width data field tabular file. Several elements also include additional variable width data field files. The element files are listed below. The "xxxxx" in the file names indicates the volume and product identification. The first three digits are equivalent to the final three digits of the volume id; the final two digits are a sequential product number.

The attached PDS labels for TES data files include the fields START_ORBIT_NUMBER and STOP_ORBIT_NUMBER. These fields refer to the beginning and ending orbits during which the data were acquired, using the TES Team orbit numbering system, also known as the Orbit Counter Keeper (ock). During the Orbit Insertion Phase, TES ock numbers and MGS Project orbit numbers were identical, except that the Project counted orbits from one periapsis to the next, while TES considered an orbit to begin at the spacecraft maneuver preceding periapsis, usually a difference of no more than twenty minutes. However, the MGS Project reset its orbit count to 1 at the beginning of the Mapping Phase. TES ock numbers were not reset, in order to preserve a unique orbit identifier. For TES data products acquired during mapping, the MGS Project mapping orbit number can be determined by subtracting 1683 from the TES ock number. During mapping, both TES and the MGS Project consider the beginning of an orbit to occur at the descending equator crossing.

One or more of the following directories: DEIMOS, MARS, or PHOBOS is/are located in the DATA Directory. These directories exist only if the specific object indicated by the name of the

directory was targeted during an orbit archived on the volume. Each directory contains applicable TES-TSDR StandardProduct element files.

TES-TSDR Standard Products are organized in time order by orbit. The number of orbits per Standard Product may vary so that an individual product contains the fewest number of integral orbits to yield a product size above 100 MB. As many TES-TSDR Standard Products are archived in a single volume as storage space allows.

File Name	File Contents
BOL.FMT	The BOL format file contains the names of all fields stored in the BOL table.
BOLxxxxx.TAB	The BOL table contains raw and calibrated visual and thermal bolometer measurements, and several properties derived from these measurements. Six BOL table records are generated for each instrument scan; one for each detector. When spectrometer data are temporally averaged, there can be up to 4 scans of bolometer data.
CMP.FMT	The CMP format file contains the names of all fields stored in the CMP table.
CMPxxxxx.TAB	The CMP table contains real and complex data from the FFT. The complex data is only down-linked when requested, and can only be requested for a single detector per observation. The CMP array contains 286 points (143 real, 143 complex) for a short scan, and 572 points (286 real, 28 record. The position of this record is stored in the "complex" column.
CMPxxxxx.VAR	Variable length record containing complex array data.
DATASET.LBL	PDS label for dataset.lst.
DATASET.LST	ASCII list of TES-TSDR file types found in the directory. This file is required for the TES vanilla software.
GEO.FMT	The GEO format file contains the names of all fields stored in the GEO table.
GEOxxxxx.TAB	The GEO table contains information about the sun/spacecraft/planet geometry in a format that is easily searchable. These values are computed for every scan other than those that could not have targeted the planet (i.e., not for reference looks). If the observation failed to hit the planet, some values can still be computed, and others are set to impossible fill values.
IFG.FMT	The IFG format file contains the names of all fields stored in the IFG table.
IFGxxxxx.TAB	The IFG table contains raw interferogram data. The interferogram data is only down-linked when requested, and can only be requested for a single detector per observation. The IFG array contains 1600 points for a short scan, and 3200 points

for a long scan. The interferogram data array is stored in a variable length record. The position of this record is stored in the "ifgm" column.

IFGxxxxx.VAR Variable length record containing interferogram data array.

LMB.FMT The LMB format file contains the names of all fields stored in the LMB table.

LMBxxxxx.TAB The LMB table contains values derived from spectra that look at the limb of Mars.

It contains one record for each limb set (sequential observations that view the limb

at different altitudes). See the lmb_quality word for information on the validity of calculated variables. The aerosol information may include data from surface

observations taken of the same geographic region at other times.

OBS.FMT The OBS format file contains the names of all fields stored in the OBS table.

OBSxxxxx.TAB The OBS table stores the state of the instrument at the start of each observation.

One OBS record is generated for each observation.

POS.FMT The POS format file contains the names of all fields stored in the POS table.

POSxxxxx.TAB The POS table stores the positions of the spacecraft and sun relative to the planet,

the spacecraft's orientation quaternion, and the Mars body quaternion, all relative to the J2000 system. This data is initially derived from the project SPICE kernels, but

may be corrected from various other sources. This table may also include

interpolated values where SPICE data was unavailable.

RAD.FMT The RAD format file contains the names of all fields stored in the RAD table.

RADxxxxx.TAB The RAD table contains the raw and calibrated observed radiances. For each

observation there can be up to 6 RAD records, one for each active spectrometer

detector.

RADxxxxx.VAR Variable length record containing raw and calibrated radiance spectra.

SRF.FMT The SRF format file contains the names of all fields stored in the SRF table.

SRFxxxxx.TAB The SRF table contains values derived from spectra that include Mars in the field of

view. It contains one record for each valid calibrated radiance which includes the

planet and for which any valid quantities could be derived.

SRFxxxxx.VAR Variable length record containing surface spectra.

TLM.FMT The TLM format file contains the names of all fields stored in the TLM table.

TLMxxxxx.TAB The TLM table stores auxiliary observation parameters. Records in the TLM table occur at a frequency less than or equal to the frequency of OBS records; that is, one (or none) per observation.

3.4. DOCUMENT Directory Contents

The following files are contained in the DOCUMENT Directory.

File Name	File Contents
ARCHSIS.ASC	The Archive Volume SIS (this document) in ASCII text.
ARCHSIS.LBL	PDS label for the Archive Volume SIS ASCII and PDF documents.
ARCHSIS.PDF	The Archive Volume SIS (this document) in PDF format.
DOCINFO.TXT	A description of the contents of this directory.
PROCESS.ASC	The TES Data Processing User Guide in ASCII text.
PROCESS.LBL	PDS label for the TES Data Processing User Guide ASCII and PDF documents.
PROCESS.PDF	The TES Data Processing User Guide in PDF format.
SDPSIS.ASC	The TES-TSDR Standard Data Products SIS (TES-TSDR) in ASCII text.
SDPSIS.LBL	PDS label for the TES-TSDR Standard Data Products SIS ASCII and PDF
	documents.
SDPSIS.PDF	The TES-TSDR Standard Data Products SIS (TES-TSDR) in PDF format.

3.5. INDEX Directory Contents

The following files are contained in the INDEX Directory.

File Name	File Contents
CLASS.TXT	A file containing information on data classification.
CUMINDEX.LBL	A PDS detached label that describes CUMINDEX.TAB.
CUMINDEX.TAB	A table listing all TES products published so far in this volume set, including the
	data on this volume.
DETMASK.TXT	A file containing information on spatial editing using detector masks.
INDEX.LBL	A PDS detached label that describes INDEX.TAB.
INDEX.TAB	A table listing all TES products on this volume.
INDXINFO.TXT	A description of the contents of this directory.
QUALITY.TXT	A file containing information on the quality fields.

SPECMASK.TAB A table listing of TES spectral masks.

SPECMASK.TXT A file containing information on spectral editing masks.

3.6. SOFTWARE Directory Contents

The following files are contained in the SOFTWARE Directory. They are subject to change during the course of the mission. The latest versions available will be put on the archive volumes.

File Name	File Contents
SOFTINFO.TXT	A description of the contents of this directory.
BIN	A directory containing the binary executables for UNIX and PC platforms.
DOC	A directory containing user documentation for the provided software.
SRC	A directory containing the source code necessary for UNIX and PC platforms.

4. Archive Volume Format

This section describes the format of TES-TSDR Standard Product Archive Volumes. Data that comprise the TES Standard Product Archives will be formatted in accordance with Planetary Data System specifications [Planetary Science Data Dictionary, 1996; PDS Data Preparation Workbook, 1995; PDS Standards Reference, 1995].

4.1. Disk Format

Archive Volumes will have a CD-ROM or DVD format that is in accordance with ISO 9660 level 1 Interchange Standard [ISO 9660, 1988]. They will be compatible with Macintosh OS, OS2, Unix, VMS, and Windows/MS-DOS computer operating systems.

4.2. File Formats

The following section describes file formats for the kinds of files contained on Archive Volumes. For more information, see the PDS Data Preparation Workbook [1995] and the PDS Standards Reference [1995].

4.2.1. Catalog File Format Catalog files (.CAT suffix) exist in the ROOT and CATALOG directories. They are formatted in an object-oriented structure consisting of sets of 'keyword = value' declarations. All catalog files have records that terminate with a carriage return character (ASCII 13) and a line feed character (ASCII 10). This allows the files to be read by Macintosh OS, OS2, Unix, VMS, and Windows/MS-DOS computer operating systems.

4.2.2. Document File Format Document files (.TXT and .ASC suffixes) exist in the ROOT, CATALOG, DATA, DOCUMENT, INDEX, and SOFTWARE directories. They are ASCII files with embedded PDS labels. All document files have records that terminate with a carriage return character (ASCII 13) and a line feed character (ASCII 10). This allows the files to be read by Macintosh OS, OS2, Unix, VMS, and Windows/MS-DOS computer operating systems.

4.2.3. PDS Label Format All data product files in the TES-TSDR Standard Product Archive Volumes have PDS labels [Planetary Science Data Dictionary, 1996; PDS Standards Reference,1995]. These labels are embedded at the beginning of the data files. For examples of PDS labels for each type of data product, see the TES-TSDR Standard Data Product SIS [TES-TSDR SIS, 1998].

Detached PDS label files (.LBL suffix), are located in the INDEX, DATA, DOCUMENT, and ROOT directories.

A PDS label, whether embedded or detached from its associated file, provides descriptive information about the associated file. The PDS label is an object-oriented structure consisting of sets of 'keyword = value' declarations; the object to which the label refers is denoted by a statement of the form:

```
^object = location
```

in which the carat character (^, also called a pointer in this context) indicates where to find the object. In an embedded label, the location is an integer representing the starting record number of the object (the first record in the file is record 1). In a detached label, the location denotes the name of the file containing the object, along with the starting record or byte number, if there is more than one object in the file. For example:

```
^HEADER = ("F01.IMG",1)
^IMAGE = ("F01.IMG",1025 <BYTES>)
```

indicates that the IMAGE object begins at byte 1025 of the file F01.IMG, in the same directory as the detached label file. Below is a list of the possible formats for the 'object definition.

```
^object = n
^object = n<BYTES>
^object = "filename.ext"
^object = ("filename.ext",n)
```

```
^object = ("[dirlist]filename.ext",n)
^object = ("filename.ext",n<BYTES>)
^object = ("[dirlist]filename.ext",n<BYTES>)
```

where n is the starting record or byte number of the object, counting from the beginning of the file (record 1, byte 1), <BYTES> indicates that the number given is in units of bytes, filename is the up to 8 character, alphanumeric upper-case file name, ext is the 3 character upper-case file extension, and dirlist is a period-delimited path-list of parent directories, in upper case, that specifies the object file directory (used only when the object is not in the same directory as the label file). The list begins at the directory level below the root directory. '[dirlist]' may be omitted when the object being described is located either in the same directory as the detached label or in a subdirectory named LABEL that is located in a higher level of the directory tree (typically root itself).

All detached labels have records that end with a carriage return character and a line feed character. This allows the files to be read by Macintosh OS, OS2, Unix, VMS, and Windows/MS-DOS computer operating systems.

- **4.2.4. Software File Format** Software files are C source code. Executable binaries will be precompiled for UNIX and PC operating systems.
- **4.2.5. Tabular File Format** Tabular files (.TAB and .VAR suffixes) exist in the INDEX and DATA directories. Tabular files are either ASCII or binary files. The TES-TSDR Standard Product element files in the DATA directory are all binary tabular files.

ASCII tabular files are formatted for direct reading into many database management systems on various computers. All fields are separated by commas, and character fields are enclosed in double quotation marks ("). Character fields are left justified and padded with spaces to keep quotation marks in the same columns of successive records. Numeric fields are right justified. The "start byte" and "bytes" values listed in the labels do not include the commas between fields or the quotation marks surrounding character fields. The records are of fixed length, and the last two bytes of each record contain the ASCII carriage return and line feed characters. This allows a table to be treated as a fixed length record file on computers that support this file type and as a text file with embedded line delimiters on those that don't.

Two types of binary tabular files are present in the TES-TSDR Standard Product Archive Volumes: fixed length data field files (.TAB suffix) and variable length data field files (.VAR suffix). Fixed length data field files always accompany variable length data field files and contain a column with a pointer to data in the variable length data field file. There are no column delimiters for binary

tabular files. For more information about the variable length data field files in TES-TSDR Standard Product Archive Volumes, see the TES-TSDR Standard Product SIS.

All tabular files are described by PDS labels that are either embedded at the beginning of the file or detached. If detached, the PDS label file has the same name as the data file it describes, with the extension .LBL; for example, the file INDEX.TAB is accompanied by the detached label file INDEX.LBL in the same directory.

5. Archive Volume Generation

5.1. Data Transfer, Validation Methods, and Production

The TES Team will produce complete TES-TSDR Standard Product Archive Volumes at Arizona State University. Archive volumes will be written to write-once CD-ROMs (CD-WOs) for distribution to Co-Investigators and the Science Data Validation Team (SDVT). The PDS Geosciences Node will also receive a CD-WO copy of each archive volume to verify that it conforms to the TES-TSDR SIS and to PDS standards for archive volumes. Copies of archive volumes may also be placed on the Internet.

Upon approval of a volume by the SDVT, the TES Team will deliver it to a vendor for replication as CD-ROMs and/or DVDs. The Team will provide the vendor with a mailing list for distribution of copies. The list will include MGS personnel who express interest in receiving the data, the Planetary Data System, and the National Space Science Data Center (NSSDC). The PDS will request enough copies to serve its anticipated user needs, and will fund those copies. The PDS will be responsible for making additional future copies as needed.

5.2. Data Product Sizes

The amount of data returned from TES is extremely variable. Each Archive Volume will contain as many TES-TSDR Standard Products as fit on the storage media. Anticipated data return for a typical mapping orbit (2-hour period) is shown in Table 2.

Product Element	2 Hour Orbit (MB)	Mission (MB)
BOL	0.604	4,961
CMP	0.020	168
GEO	0.961	7,689
IFG	0.115	924

Table 2 - TES-TSDR Standard Product Element Nominal Sizes

TOTAL	24.545	201,345
TLM	0.040	332
SRF	8.105	64,840
RAD	12.873	102,984
POS	1.512	12,096
OBS	0.140	1,120
LMB	0.172	1,376

5.3. Labeling and Identification

Each TES-TSDR CD-WO to be sent to an institution for evaluation will bear a volume ID using the last two components of the volume set ID [PDS Standards Reference, 1995]. The volume set ID will be USA_NASA_JPL_MGST_xxxx. Where xxxx indicates both version and mission phase. The first digit indicates data version, with 0 = original release, 1 = first revision, 2 = second revision and so on. The last three digits indicate mission phase using the following convention:

001 - 020	Aerobrake Phase One
021 - 040	Science Phasing Orbits One
041 - 060	Science Phasing Orbits Two
061 - 080	Aerobrake Phase Two
100 - 999	Mapping

Hence the first volume will have the volume ID MGST_0001.

6. Cognizant Persons and Support Staff

Table 3 - TES-TSDR Archive Volumes Support Staff

TES Team

Kelly C. Bender

Data Producer Arizona State University
Department of Geology

Box 871404

Tempe, Arizona 85287-1404 480-965-4183 kcbender@asu.edu

0.071404

Philip R. Christensen

TES Principal Investigator Arizona State University

Department of Geology

Box 871404

Tempe, Arizona 85287-1404 480-965-7105 phil@east.la.asu.edu

Kimberly C. (Feely) Murray

Data Producer Arizona State University

Department of Geology

Box 871404

Tempe, Arizona 85287-1404 480-965-8056 kim.murray@asu.edu

Noel S. Gorelick

Data Producer Arizona State University

Department of Geology

Box 871404

Tempe, Arizona 85287-1404 480-965-7829 gorelick@asu.edu

Greg L. Mehall

TES Instrument Manager Arizona State University

Department of Geology

Box 871404

Tempe, Arizona 85287-1404 480-965-3063 mehall@asu.edu

Washington University

Raymond E. Arvidson

MGS Interdisciplinary Scientist Washington University

Campus Box 1169 One Brookings Drive

St. Louis, MO 63130 314-935-5679 arvidson@wunder.wustl.edu

Ed Guinness

WU TES Archive Manager Washington University

Campus Box 1169 One Brookings Drive

St. Louis, MO 63130 314-935-5744 guinness@wunder.wustl.edu

APPENDIX A: Volume Directory Structure

Below is a representation of the directory structures of a TES Archive Volume. Names without extensions are directory names (e.g. CATALOG), while names with extensions are file names (e.g. CATINFO.TXT).

ROOT |----- AAREADME.HTM |----- AAREADME.LBL |----- AAREADME.TXT ----- ERRATA.TXT |----- VOLDESC.CAT ----- CATALOG ----- CATINFO.TXT |---- DATASET.CAT |---- DEITGT.CAT |---- INST.CAT |----- INSTHOST.CAT |---- MARTGT.CAT |---- MISSION.CAT |----- PERSON.CAT |-----PHOTGT.CAT ---- REF.CAT ---- DATA |---- DATAINFO.TXT |----- ENB.TXT |----- GEOMETRY.TXT |----- WAVNUMDS.LBL |----- WAVNUMDS.TAB |----- WAVNUMSS.LBL |----- WAVNUMSS.TAB ---- DEIMOS ---- BOL.FMT |---- BOLxxxxx.TAB |----- CMP.FMT |---- CMPxxxxx.TAB |----- CMPxxxxx.VAR |---- DATASET.LBL |----- DATASET.LST

	GEO.FMT
	GEOxxxxx.TAB
	IFG.FMT
	IFGxxxxx.TAB
	IFGxxxxx.VAR
	LMB.FMT
	LMBxxxxx.TAB
	OBS.FMT
	OBSxxxxx.TAB
	POS.FMT
	POSxxxxx.TAB
	RAD.FMT
	RADxxxxx.TAB
	RADxxxxx.VAR
	SRF.FMT
	SRFxxxxx.TAB
	SRFxxxxx.VAR
	TLM.FMT
	TLMxxxxx.TAB
	VAR.LBL
	MARS
	BOL.FMT
	BOLxxxxx.TAB
	CMP.FMT
	CMPxxxxx.TAB
	CMPxxxxx.VAR
	DATASET.LBL
	DATASET.LST
	GEO.FMT
	GEOxxxxx.TAB
	IFGxxxxx.TAB
	IFGxxxxx.VAR
	LMB.FMT
	LMBxxxxx.TAB
	OBS.FMT
	OBSxxxxx.TAB

RAD.FMT	
RADxxxxx.TAB	
RADxxxxx.VAR	
SRF.FMT	
SRFxxxxx.TAB	
SRFxxxxx.VAR	
TLM.FMT	
TLMxxxxx.TAB	
VAR.LBL	
PHOBOS	
BOL.FMT	
BOLxxxxx.TAB	
CMP.FMT	
CMPxxxxx.TAB	
CMPxxxxx.VAR	
DATASET.LBL	
DATASET.LST	
GEO.FMT	
GEOxxxxx.TAB	
IFG.FMT	
IFGxxxxx.TAB	
IFGxxxxx.VAR	
LMB.FMT	
LMBxxxxx.TAB	
OBS.FMT	
OBSxxxxx.TAB	
POS.FMT	
POSxxxxx.TAB	
RAD.FMT	
RADxxxxx.TAB	
RADxxxxx.VAR	
SRF.FMT	
SRFxxxxx.TAB	
SRFxxxxx.VAR	
TLM.FMT	
TLMxxxxx.TAB	
VAR.LBL	
DOCUMENT	
ARCHSIS.ASC	

	ARCHSIS.LBL
	ARCHSIS.PDF
	DOCINFO.TXT
	PROCESS.ASC
1	PROCESS.LBL
	PROCESS.PDF
	SDPSIS.ASC
	SDPSIS.LBL
	SDPSIS.PDF
	INDEX
	CLASS.TXT
	CUMINDEX.LBL
	CUMINDEX.TAB
	DETMASK.TXT
	INDEX.LBL
	INDEX.TAB
	INDXINFO.TXT
	QUALITY.TXT
	SPECMASK.TAB
	SPECMASK.TXT
	SOFTWARE
	SOFTINFO.TXT
	BIN
	BININFO.TXT
	HPPA2.EXE
	INDIGO2.EXE
	LINUX.EXE
	RS6K.EXE
	SOLSPARC.EXE
	DOC
	DOCINFO.TXT
	USERDOC.TXT
	SRC
	BUFFS.C
	CONVERT.C
	DATASET.C
	DIR.C
1	L 200 H

	FAKE.C
	FAKE.H
	FF_IRTM.C
	FF_IRTM.H
	FF_T20.C
	FIELDS.C
	GENDEF.H
	HEADER.C
	HEADER.H
	IO_LABLIB3.C
	IO_LABLIB3.H
ĺ	MAKEFILE
	MEM.C
	MEM.H
	OUTPUT.C
	OUTPUT.H
	PROTO.H
	SEARCH.C
	SELECT.C
	SRCINFO.TXT
	SYSTEM.C
	SYSTEM.H
	TOOLBOX.H
	TOOLS.C
	TOOLS.H
	VANILLA.C
	VERSION.H